



Control System

- ① Inline Connection
- ② Head Unit

Entertainment & Convenience System

- ③ Rear Seat Display
- ④ Rear Seat Entertainment Module
- ⑤ Display
- ⑥ Rear Seat Display

Safe & Security System

- ⑦ Side View Camera
- ⑧ Camera Module
- ⑨ Rear View Camera
- ⑩ Side View Camera
- ⑪ Front View Camera

Information System

- ⑫ USB Connection
- ⑬ USB Connection

HSD SPECIFICATIONS

Electrical

| | |
|---------------------------------|---|
| Impedance | 100 Ohm |
| Frequency Range | DC- 2 GHz |
| Insertion Loss | 0.1 dB max from DC – 2 GHz |
| Insulation Resistance | 1000 MΩ MIN. |
| Contact Resistance | |
| Center Contact | ≤ 10 MΩ MIN. |
| Outer Contact | ≤ 7.5 MΩ MIN. |
| Dielectric Withstanding Voltage | At Sea Level: > 250 VRMS (Interface only) |

Environmental

| | |
|-------------------|---------------------|
| Temperature Range | - 40°C to +105°C |
| Thermal Shock | DIN EN 60068- 2- 14 |
| Vibration | DIN EN 60068- 2- 64 |
| Mechanical Shock | DIN EN 60068- 2- 27 |